

Floor Marking Tapes / Floor Tapes / Marking Tapes / Hazard Tapes / Lane Marking Tapes



Technical Characteristics:

Type of Testing	Unit	Typical Value	Test Method
Total Thickness	Micron	165 micron	IS:8402
Pees Adhesion (ATS)	g / 25 mm	Min 1000 grms	ASTMD:1000
Tack Rolling Ball	Ball No.	Min 6	ASTMD:1000
Solvent Resistance	-	Above average	N/A
Weather Resistance	-	Good	N/A
Heat Resistance	1 hr	100	N/A

Sizes Available :

a)	Size :	24 mm(1 Inch)	X 33 Meter
b)	Size :	36 mm(1½ Inch)	X 33 Meter
c)	Size :	48 mm(2 inch)	X 33 Meter
d)	Size :	72 mm(3 inch)	X 33 Meter
e)	Size :	96 mm(4 inch)	X 33 Meter
f)	Size :	120 mm(5 inch)	X 33 Meter
g)	Size :	144 mm(6 inch)	X 33 Meter

- Floor marking tapes are being widely used now a day for safety, identifying lane marking for storage segmentation, ideal for ISO 9001, QS 9000 companies, good resistance to chemical and other moving objects. Better than paints
- Available in various sizes and colors
- Colors available are white, Yellow, Blue, Green, Black, Red, Yellow- Black, Red-white, Green White & Mor



STATIC SYSTEMS
TOTAL SOLUTION FOR ELECTRONIC INDUSTRIES

Product Data Sheet
